




## **CERAMIC RIBBON SERIES FUSION SPLICE PROTECTION SLEEVE**

**Splice Technologies' "CERAMIC RIBBON"** Series fusion splice protection sleeve is designed to accommodate **2 – 12** ribbon fiber. This product is constructed with an EVA meltable adhesive inner tube, a polyolefin heat shrink outer tube, and either single or dual ceramic strength members. Our single strength member sleeve has an after shrink diameter of **4.9 X 4.4mm**. Our dual strength member sleeve is designed to "sandwich" the ribbon, thus minimizing any undue stress on the fiber, while maximizing fiber uniformity and retentivity. This option has an after shrink diameter of **5.7 X 4.9mm**. These products utilize solid white ceramic strength members and are a lower cost alternative to our clear glass strength member products. The entire assembly is designed to ensure that all members maintain perfect alignment during shipping, handling and shrinking. We are proud to say that all of our products are made here in the **USA** and most sleeves are in stock ready for immediate delivery.

### **FEATURES**

- Bellcore GR-1380 Compliant
- RoHS & REACH Compliant
- Outer tube meets SAE AMS-DTL-23053/5 Class 2
- Inner EVA meltable adhesive tube
- Full length strength member for total fiber support
- Close dimensional tolerances
- Open ended assembly minimizing possibility of air entrapment during heat shrinking
- Operating Temperature Range -55°C to +110°C
- Packaged in 25 per bag



### **PART NUMBER KEY**

MFSS-SM40 40mm length w/single ceramic member  
MFSS-MM40 40mm length w/two ceramic members

### **FOR ORDERS AND QUOTES**

Phone: 1-631-924-8108  
Fax: 1-631-924-8109  
Email: [sales@splicetechnologies.com](mailto:sales@splicetechnologies.com)  
Website: [www.splicetechnologies.com](http://www.splicetechnologies.com)