





**SPLICE SLEEVE HOLDERS –
FSH/SSH SERIES**

Commonly called splice “chips” or “holders” these devices are designed to secure a variety of mechanical and fusion splice protection sleeves, as well as other types of fiber optic devices. Splice Technologies’ manufactures a wide variety of holders utilizing engineered materials. All of our holders are designed with a high-peel tape adhesive for mounting into splice trays and closures.

<u>Model Number</u>	<u>Holder Material</u>	<u>Holder Specifications</u>	<u>Adhesive Tape Material</u>	<u>Tape Specifications</u>
FSH-HS-06	 Black Low Density Polyethylene	Density = 0.924 g/cm ³ Shore D Hardness = 55 Vicat Softening Temp. = 210°F Brittleness Temp. = -90°F 1.00" X 1.09" X 0.21" L X W X H	Polyethylene Foam Tape w/ Rubber Adhesive, White in color.	Thickness = 0.03 inches Peel Adhesion = 8 lb/in width Solvent Resistance = Medium Operating Temperature -20°F to +158°F
FSH-SL-06	 Black Crosslinked Low Density Polyethylene Foam	Operating Temp. = -90°F to +185°F Tensile Strength = 65 psi Elongation@ Break = 130% L X W X H 1.50" X 1.25" X 0.18"	Double-coated Nonwoven Acrylic Adhesive Tape, Clear	Operating Temperature -55°F to +190°F
SSH-S12	 Black, High Density Silicone Rubber	Operating Temp. = -55°F to +250°F Tensile Strength = 7.0 MPa Elongation@ Break = 320% L X W X H 2.75" X 0.50" X 0.25"	3M Double-coated polyester film w/Silicone/Acrylic Adhesive Tape, Clear	Operating Temperature -55°F to +176°F
SSH-R12	 Blue, High Density Silicone Rubber	Operating Temp. = -55°F to +250°F Tensile Strength = 7.0 MPa Elongation@ Break = 320% L X W X H 2.95" X 0.50" X 0.29"	3M Double-coated polyester film w/Silicone/Acrylic Adhesive Tape, Clear	Operating Temperature -55°F to +176°F

FOR ORDERS AND QUOTES:

Phone: 1-631-924-8108
Fax: 1-631-924-8109
Email: sales@splicetechnologies.com
Website: www.splicetechnologies.com