


THIN SERIES FUSION SPLICE PROTECTION SLEEVE

Splice Technologies' "Thin" series fusion splice protection sleeve is similar to our "Slim" series product with the exception of a further reduced after shrink diameter of **2.3mm** making it our thinnest offered splice sleeve with a strength member in a 60mm length. The robust design and user friendly size will accommodate fiber diameters up to **1.4mm**, and are available in 40 and 60mm lengths. This product is constructed with an inner EVA meltable adhesive tube, stainless steel strength member and a polyolefin heat shrink outer tube. The tubes are clear to allow viewing the color of the fiber after splicing. This product has been proportionately downsized using the same core materials, formulations and manufacturing processes that are used in our "Standard" series product. The entire assembly is heat bonded to ensure that all members maintain perfect alignment during shipping, handling and shrinking. We are proud to say that all of our products are made here in the USA and most sleeves are in stock ready for immediate delivery.

FEATURES

- RoHS & REACH Compliant
- Outer tube meets SAE AMS-DTL-23053/5 Class 2
- Inner EVA meltable adhesive tube
- Full length strength member for total fiber support
- Close dimensional tolerances
- Heat bonded assembly
- Open ended assembly minimizing possibility of air entrapment during shrinkage
- Packaged in 100 per bag



PART NUMBER KEY

FSS-TC40 40mm length
FSS-TC60 60mm length

FOR ORDERS AND QUOTES

Phone: 1-631-924-8108
Fax: 1-631-924-8109
Email: sales@splicetechnologies.com
Website: www.splicetechnologies.com